kastamonu

SPECIFICATIONS

LLC "KASTAMONU INTEGRATED WOOD INDUSTRY"			PRODUCT	BLU33TV - 8X193X1380
Control settings		**Standard**	**Measurement unit**	**Tolerance Range**
Thickness		EN 13329	mm.	t max.- t min. ≤ 0,5
Density		EN 323	kg/m³	880 ± 10
Width		EN 13329	mm.	193± 0,2
Length		EN 13329	mm.	1380± 0,5
Rectangularity		EN 13329	mm.	Max. 0,2
Straightness		EN 13329	mm.	< 0,414 mm
Width flatness	**convexity, not more than**	EN 13329	mm.	< 0,386 mm
	concavity, not more than	EN 13329	mm.	< 0,289 mm
Length flatness	**convexity, not more than**	EN 13329	mm.	< 13,80 mm
	concavity, not more than	EN 13329	mm.	< 6,90 mm
Resistance to abrasion		EN 13329	turnovers	≥ 6000
Abrasion class		EN 13329	class	AC5
Impact resistance		EN 13329	class	IC3
Resistance to staining		EN 14323	score	not less than 5
Resistance to a smoldering cigarette		EN 14323	score	not less than 4
Thickness swelling		EN 13329	%	≤ 15

Chief of department quality and certification /Svetlana Klymenko/

KASTAMONU INTEGRATED WOOD INDUSTRY LLC
INN 1646027030 KPP 164601001 OGRN 1101674000416
SEZ "Alabuga", SH-3 street, building 3/3
Elabuga, Tatarstan, 423600, Russia
Phone/fax +7 85557 5 31 00 /76
www.kastamonu.ru